

PRODUCT DATA SHEET

SUPER SHUTTER

Description

SUPER SHUTTER is a Mineral oil based releasing agent for the construction and pre-cast industry. **SUPER SHUTTER** is specifically designed for superior off-shutter finishes

Principal uses

- A simple one coat application.
- An economical release agent for timber, steel and fibreglass shuttering.
- Super shutter does not evaporate in the sun.
- Build up on the shutter or mould is eliminated.
- Coverage is approximately 14-20 square metres per litre.
- Cleaning is minimised

Performance data

Appearance: Light/Medium coloured Oil
Temperature Stability: 40°C
Flash Point: 198°C
Odour: Slight
Viscosity: 46
Physical Form: Liquid

Application

Apply as thinly as possible to entire surface of shutter or mould by means of a paint brush, paint roller or low pressure spray.

Packaging

SUPER SHUTTER is available in 1000ℓ, 210ℓ and 25ℓ drums

Safety & handling

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

Shelf Life & Storage

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note

Roll the drum before use to prevent settling out of the product.

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to EpoXerite quality control. We cannot be held responsible or liable, directly or in indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.