

PRODUCT DATA SHEET

SHUTTER-OFF

Description

Shutter-off is a hydrocarbon shutter release agent for various concrete related industries

Principal uses

This product is designed specifically for timber and steel applications where a hassle free release is essential

Properties

- One coat application
- UV Stable
- Does not flash off in direct sun light
- Zero build up on shutter
- Economical

Performance data

Appearance:	Dark
Temperature Stability	40°C
Flashpoint	198°C
Odour	Slight
Viscosity	±46
Physical Form	Liquid

Application

By paint roller, brush or low pressure spray. Apply as thinly as possible to the entire surface of the shutter. Coverage is approximately 10 square metres per litre.

Packaging

The following sizes are available; 210lt & 25lt

Shelf life & storage instructions

6 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Limitations

As SHUTTER-OFF has a dark colour some staining of the concrete may occur. Where concrete finish is critical use **SUPER SHUTTER**.

As **SHUTTER-OFF** is a laundered oil, the colour and viscosity may vary. Always roll the drum before using to ensure no settlement of the ingredients has taken place.

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to EpoXerite quality control. We cannot be held responsible or liable, directly or in indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.